

UPS Technical Specification

Manufacturer's declaration in accordance with IEC 62040-3

Subclause	Characteristic of Equipment	Manufacturer's Declared Values
CONSTRUCTION		
	Model catalogue reference	9355-15-NC-0 /-MBS (UPS) 9355-15-N-xx-32 /-MBS (UPS + 1 bat part) 9355-15-N-xx-64 /-MBS (UPS + 2 bat part)
	Model rating	15 kVA / 13.5 kW; 400 VAC
	Classification	VFI-SS-111
MIL 217	MTBF	150 000 h
	Dimensions length x depth x height	305 x 702 x 420 mm (UPS) 305 x 702 x 817 mm (UPS + 1 bat part) 305 x 702 x 1214 mm (UPS + 2 bat part)
	Weight without batteries	60 kg (UPS) 75 kg (UPS + 1 bat part) 90 kg (UPS + 2 bat part) +15 kg (MBS option if selected) 65 kg (2 bat part, external) 95 kg (3 bat part, external)
	Weight with batteries if integrated	165 kg (UPS + 1 bat part) 275 kg (UPS + 2 bat part) 195 kg (2 bat part, external) 310 kg (3 bat part, external)
ENVIRONMENTAL		
4.1.4	Ambient storage temperature range	-25 to +55°C in the protective package
4.1.2	Ambient service temperature	<u>Power electronics part:</u> +0 to +40°C, max. +45°C with 7.5% derating; <u>Battery part:</u> +5 to +25°C without reducing the life time;
4.1.1	Maximum service altitude	1000 m (3300 ft) above sea level, max. 2000 m (6600 ft) with 1% derating per +100 m (330 ft)
4.1.3	Relative humidity range	5 to 95%, no condensation allowed
EN 60529	Degree of protection	IP20
7.3	Acoustic noise at 1 m - Normal mode - Stored energy	50 dBA 55 dBA
ELECTRICAL CHARACTERISTICS – INPUT		
5.2.2 and 6.3.2.1	Rated input voltage and voltage tolerance	Rectifier input: 3x230/400 V nominal; <u>Tolerance:</u> 175/305-276/480 (±20%) at 100% load 115/200-276/480 (-50%, +20%) at 50% load Bypass input: 3x230/400 V nominal; <u>Tolerance:</u> 196/340-253/438 V (-15%, +10%)
5.2.2 and 6.3.2.2	Rated input frequency and frequency tolerance	50 or 60 Hz, tolerance 45-65 Hz
5.2.2 and 6.3.10	Rated input current	21.8 A r.m.s (three phase input)
5.2.2 and 6.3.9.2	Maximum input current	29 A r.m.s (three phase input)
5.2.2	Input current distortion at rated input current	< 5% THD
5.2.2 and 6.3.10	Input power factor	0.99
5.2.2 and 6.3.3	Inrush current	<100% of rated current
5.2.2	Number of input phases	3 Phases + N (three phase input)
OUTPUT WAVEFORM		
5.3.1.2	Waveform – Normal mode	Sine waveform
5.3.1.2	Waveform – Stored energy mode	Sine waveform

UPS Technical Specification
Manufacturer's declaration in accordance with IEC 62040-3

Subclause	Characteristic of Equipment	Manufacturer's Declared Values
	Transfer – Normal mode / Stored energy	No break
	Break time / make time	No break
ELECTRICAL OUTPUT CHARACTERISTICS - STATIC CHARACTERISTICS - NORMAL MODE		
5.3.2	Rated output voltage	220/380, 230/400, 240/415 Vac, three phase
	Output voltage variation	±3 V r.m.s
	Crest factor	3
	Rated output frequency (nominal)	50 (default) or 60 Hz
6.3.2.2	Output frequency variation (synchronised if applicable)	±2 (default), ±0.5, or ±1 Hz with slew rate 1 Hz/s (default), 7 Hz/s, 3 Hz/s, 2 Hz/s, or ±0.5 Hz/s
6.3.2.3	Output frequency synchronised phase error at change of mode	Max. 8 degrees
	Rated output apparent power	15 kVA
	Rated output active power across linear load	13.5 kW
	Rated output active power across a reference (p.f. 0.7) non-linear load	10.5 kW
6.3.4.2	Total voltage distortion across a linear load	< 3%
6.3.8.1	Total voltage distortion across a reference non-linear load	5%
6.3.4.2	Individual harmonics voltage	See separate declaration
5.3.2 and 6.3.5.3	Short circuit capability	55 A, < 300 ms
5.3.2 and 6.3.5.1	Overload capability	<p>Without bypass:</p> <p>10 min >100...110% load 1 min >110...125% load 5 sec >125...150% load</p> <p>With bypass:</p> <p>Continuous >100...125% load 10 min >125...150% load 5 ms 1000% load</p> <p>Note! Selected bypass fuses may limit the overload capability.</p>
5.3.2 and 6.3.4	Range of load power factor permitted - linear load	0.7 lagging – 0.9 leading
	Number of output phases	3 Phase
5.3.2 and 6.3.4.5	Output voltage unbalance at reference unbalance load (multiphase only)	-
5.3.2 and 6.3.4.5	Maximum phase angle variation (multiphase only)	-
ELECTRICAL OUTPUT CHARACTERISTICS - DYNAMIC CHARACTERISTICS - NORMAL MODE		
5.3.2 and 6.3.6.1 and 6.3.6.2	Output voltage dynamic variation during transfer normal/stored energy mode of operation and vice versa	0%
6.3.7.1 and 6.3.8.4	Output voltage dynamic variation due to load changes	± 5% with 1 ms recovery (from 10% to 90% load step)
	Maximum rate of change of output frequency	0.5 (default), 2.5, or 7.5 Hz/s

UPS Technical Specification
Manufacturer's declaration in accordance with IEC 62040-3

<i>Subclause</i>	<i>Characteristic of Equipment</i>	<i>Manufacturer's Declared Values</i>
ELECTRICAL OUTPUT CHARACTERISTICS - STATIC CHARACTERISTICS - STORED ENERGY		
5.3.1	Rated output voltage	220/380, 230/400, 240/415 Vac, three phase
6.3.4.4	Output voltage variation	±3 V r.m.s
	Crest factor	3
6.3.4.3	Rated peak output voltage	325 V
6.3.4.4	Rated peak output voltage variation	±20 V
5.3.1.2	Non-sinusoidal voltage rise time 0,1 to 0,9 peak (if waveform exceeds 0,5 V/µs)	-
5.3.2	Output frequency	50 Hz (default) or 60 Hz
5.3.2	Output frequency variation	±0,005 Hz (single), ±0,07 Hz (parallel)
5.3.2	Rated output apparent power	15 kVA
5.3.2	Rated output active power	13.5 kW
5.3.2	Rated output active power non-linear load	13.5 kW
6.3.4.4	Total output voltage distortion	5% THD
6.3.4.4	Individual harmonic voltages - linear load	-
6.3.2 and 6.3.8.2	Individual harmonic voltages - non-linear load	-
5.3.2 and 6.3.5.4	Short circuit capability	55 A, <300 ms
5.3.2 and 6.3.5.2	Overload capability	10 min >100...110% load 1 min >110...125% load 5 sec >125...150% load 300 ms >150% load
5.3.2	Range of load power factors permitted	0.7 lagging – 0.9 leading
5.3.2	Number of output phase (multiphase only)	3 Phase
ELECTRICAL OUTPUT CHARACTERISTICS - DYNAMIC CHARACTERISTICS - STORED ENERGY		
6.3.6.1	Output voltage dynamic variation during transfer from stored energy mode to normal mode	0%
6.3.7.1	Output voltage dynamic variation due to load changes	±5% with 1 ms recovery (from 10% to 90% load step)
EFFICIENCY		
6.6.11	Efficiency Input / Output	91% at 100% rated load 91% at 75% rated load 90% at 50% rated load 86% at 25% rated load
	Heat dissipation	1330 W at 100% rated load 731 W at 50% rated load 417 W at 0% rated load
SYNCHRONIZATION (if applicable)		
6.3.6.4	Acceptable voltage difference	±25%
6.3.2.2	Range of frequency synch	±2 (default), ±0.5, or ±1 Hz with slew rate 1 Hz/s (default), 7 Hz/s, 3 Hz/s, 2 Hz/s, or ±0.5 Hz/s
6.3.6.4	Maximum phase error	8 degrees

UPS Technical Specification
Manufacturer's declaration in accordance with IEC 62040-3

<i>Subclause</i>	<i>Characteristic of Equipment</i>	<i>Manufacturer's Declared Values</i>
5.4 STORED ENERGY MODE OF OPERATION		
	Duration of maximum permitted stored energy time at rated load	No limit.
6.3.9.1	Stored energy time (for integral batteries) at rated load	See separate declaration
6.3.9.2	Restored energy time to 90% charge (for integral batteries) Battery rating and quantity (for integral battery) Battery recharge profile	Max. 10 h recommended 7 Ah and 32 units (VRLA), max. battery voltage 192*2.35V = 455V ABM = 90% resting, 10% float charging
6.3.9.1	Battery cut-off voltage	1.75 / 1.67 VPC
5.8 CONTROL AND MONITORING SIGNALS		
5.8	See separate declaration for complete list of indications and remote alarm/monitoring or interface devices	See User's Manual
5.5.2 BYPASS CHARACTERISTICS		
5.5.2	Type of bypass	Manual and Automatic
5.5.2	Mechanical/static	Mechanical Static
5.5.2	No break transfer / break transfer	No break
5.5.2	Break time / make time	No break
5.5.2	Maintenance bypass	Yes (optional without)
5.5.2	Bypass protection fuse or circuit-breaker rating	25 A
5.5.2	Galvanic isolation fitted	No
5.7 ELECTROMAGNETIC COMPATIBILITY		
	Immunity, see IEC 62040-2	Yes
	Emission, see IEC 62040-2	Yes