



KL3222 | 2-channel input terminal PT100 (RTD) for 4-wire connection, high-precision

The KL3222 analog input terminal allows resistance sensors to be connected directly. Linearisation over the full temperature range is realised with the aid of a microprocessor. The temperature range can be selected freely. The Bus Terminal's standard settings are: resolution 0.01 °C in the temperature range of PT100 sensors in 4-wire connection. The run LEDs give an indication of the data exchange with the Bus Coupler. The error LEDs indicate sensor faults (e.g. a broken wire).

Technical data	KL3222 KS3222
Number of inputs	2
Power supply	via the K-bus
Technology	4-wire
Sensor types	PT100, PT200, PT500, PT1000, Ni100, Ni120, Ni1000 resistance measurement (e.g. potentiometer, $10\ \Omega\dots1.2/5\ k\Omega$), KTY
Connection method	4-wire
Measuring range	-200...+850 °C (PT sensors); -60...+250 °C (Ni sensors); -200...+320 °C (high-precision)
Conversion time	typ. 50 ms
Measuring current	typ. 0.5 mA
Resolution	0.01 °C per digit
Measuring error	0.1 °C at 40 °C ambient temperature, 4-wire connection, PT100 sensors and 50 Hz filter
Electrical isolation	500 V (K-bus/signal voltage)
Current consumption power contacts	—
Current consumption K-bus	typ. 60 mA
Bit width in the process image	input: 2 x 16 bit data (2 x 8 bit control/status optional)
Configuration	no address setting, configuration via Bus Coupler or controller
Special features	open-circuit recognition, high-precision
Weight	approx. 70 g
Operating/storage temperature	0...+55 °C/-25...+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 20/variable
Pluggable wiring	for all KSxxxx Bus Terminals
Approvals	CE, UL, Ex